

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Pu Speedcoat hardener
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU21 Consumer uses: Private households / general public / consumers
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Process category
 - PROC11 Non industrial spraying
 - PROC7 Industrial spraying
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category
 - AC7 Metal articles
 - AC11 Wood articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- Uses advised against
This product is not recommended for applications other than the uses identified above.
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
Oosteinderweg 32
1432 AL Aalsmeer
Netherlands
tel.+31 297-360366
email: info@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number: +61 7 5563 1222 (Monday-Friday 8:30am-5:00pm)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3

H226

Flammable liquid and vapour.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 1)



GHS07

Acute Tox. 4	H332	Harmful if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
.....		
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS07

- Signal word Warning
- Hazard-determining components of labelling:
 - Hexamethylene-1,6 diisocyanate homopolymer
 - reaction mass of ethylbenzene and xylene
 - Heptan-2-one
 - Hydrocarbons, C9, aromatics.
 - Hexamethylene diisocyanate
- Hazard statements
 - H226 Flammable liquid and vapour.
 - H332 Harmful if inhaled.
 - H317 May cause an allergic skin reaction.
 - H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 - H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
 - P102 Keep out of reach of children.
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 - P271 Use only outdoors or in a well-ventilated area.
 - P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 - P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

**Safety data sheet
according to UK REACH**

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 2)

- Additional information:
Contains isocyanates. May produce an allergic reaction.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT:
The product does not meet the criteria for PBT in accordance with UK REACH Annex XIII.
- vPvB:
The product does not meet the criteria for vPvB in accordance with UK REACH Annex XIII.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 28182-81-2 EC number: 931-274-8 Reg.nr.: 01-2119485796-17	Hexamethylene-1,6 diisocyanate homopolymer ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics. ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336	2.5-10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	2.5-10%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32	reaction mass of ethylbenzene and xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥2.5-<10%

(Contd. on page 4)

**Safety data sheet
according to UK REACH**

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 3)

CAS: 110-43-0 EINECS: 203-767-1 Index number: 606-024-00-3 Reg.nr.: 01-2119902391-49	Heptan-2-one Flam. Liq. 3, H226 Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H336	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	N-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	≤2.5%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37	Hexamethylene diisocyanate Acute Tox. 3, H331 Resp. Sens. 1, H334 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 Specific concentration limits: Resp.Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	<0.1%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 4)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required

(Contd. on page 6)

**Safety data sheet
according to UK REACH**

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 5)

- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
100 mg/m³, 19 ppm, TWA Manuf. data

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

110-43-0 Heptan-2-one

WEL	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk
-----	--

123-86-4 N-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

822-06-0 Hexamethylene diisocyanate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

- Regulatory information WEL: EH40/2020
- DNEL (Derived No Effect Level) voor professionals

128601-23-0 Hydrocarbons, C9, aromatics.

Oral	Long-term -systemic effects.	11 mg/kg/dag (consumer)
Dermal	Long-term - systemic effects.	11 mg/kg/dag (consumer)
Inhalative	Long-term - systemic effects.	32 mg/m ³ (consumer)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	Long-term - systemic effects.	36 mg/kg/dag (consumer)
Dermal	Long-term - systemic effects.	320 mg/kg/dag (consumer)
Inhalative	Long-term - systemic effects.	33 mg/m ³ (consumer)

110-43-0 Heptan-2-one

Oral	Long-term - systemic effects.	23.32 mg/kg/dag (consumer)
Dermal	Long-term - systemic effects.	23.32 mg/kg/dag (consumer)
Inhalative	Long-term - systemic effects.	84.31 mg/m ³ (consumer)

123-86-4 N-butyl acetate

Oral	Long-term - systemic effects.	2 mg/kg bw/dag (consumer)
	Short-term - systemic effects	2 mg/kg bw/dag (consumer)
Dermal	Short-term - systemic effects	6 mg/kg/bw/dag (consumer)

(Contd. on page 7)

**Safety data sheet
according to UK REACH**

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 6)

Inhalative	Long-term - systemic effects	3.4 mg/kg bw/dag (consumer)
	Long-term - systemic effects.	12 mg/m ³ (consumer)
	Long-term - local effects.	300 mg/m ³ (consumer)
	Short-term systemic effects.	300 mg/m ³ (consumer)
	Short term - local effects.	300 mg/m ³ (consumer)

· DNEL (Derived No Effect Level) for general audience

28182-81-2 Hexamethylene-1,6 diisocyanate homopolymer

Inhalative	Short-term - local effects.	1 mg/m ³ (Employees)
	Long-term - local effects.	0.5 mg/m ³ (Employees)

128601-23-0 Hydrocarbons, C9, aromatics.

Dermal	Long-term - systemic effects.	25 mg/kg/dag (Employees)
Inhalative	Lange termijn systemische effecten.	150 mg/m ³ (Employees)

108-65-6 2-methoxy-1-methylethyl acetate

Dermal	Long-term - systemic effects.	796 mg/kg/dag (Employees)
Inhalative	Long-term - systemic effects.	275 mg/m ³ (Employees)

110-43-0 Heptan-2-one

Dermal	Long-term - systemic effects.	54.27 mg/kg/dag (Employees)
Inhalative	Lange termijn systemische effecten.	394.25 mg/m ³ (Employees)
	Short-term - systemic effects.	1,516 mg/m ³ (Employees)

123-86-4 N-butyl acetate

Dermal	Long-term - systemic effects.	7 mg/kg/dag (Employees)
Inhalative	Short-term - systemic effects	11 mg/kg/dag (Employees)
	Lange termijn systemische effecten.	48 mg/m ³ (Employees)
	Short-term - systemic effects.	600 mg/m ³ (Employees)
	Short-term - local effects.	600 mg/m ³ (Employees)
	Long-term - local effects.	300 mg/m ³ (Employees)

822-06-0 Hexamethylene diisocyanate

Inhalative	Lange termijn systemische effecten.	0.035 mg/m ³ (Employees)
	Short-term - local effects.	0.07 mg/m ³ (Employees)
	Short-term - systemic effects	0.07 mg/m ³ (Employees)
	Long-term - local effects.	0.035 mg/m ³ (Employees)

· PNECs

28182-81-2 Hexamethylene-1,6 diisocyanate homopolymer

Sewage treatment plant	38.3 mg/l (Sewage treatment plant)
Freshwater	0.127 mg/l (Freshwater)
Marine water	0.0127 mg/l (Marine water)

(Contd. on page 8)

**Safety data sheet
according to UK REACH**

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 7)

Sediment (freshwater)	0.01334 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.001334 mg/kg sed dw (Marine water)
Soil	26,670 mg/kg (Marine water)
	266,700 mg/kg (Freshwater)
Soil	53,182 mg/kg (soil)
108-65-6 2-methoxy-1-methylethyl acetate	
Food chain	100 mg/l (Food chain)
Sewage treatment plant	100 mg/l (Sewage treatment plant)
Freshwater	6.35 mg/l (Freshwater)
Marine water	0.0635 mg/l (Marine water)
Sediment (freshwater)	3.29 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.329 mg/kg sed dw (Marine water)
Soil	0.29 mg/kg (soil)
110-43-0 Heptan-2-one	
Intermittent	0.982 mg/l (Freshwater)
Freshwater	0.098 mg/l (Freshwater)
Marine water	0.01 mg/l (Marine water)
Sediment (freshwater)	1.89 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.189 mg/kg sed dw (Marine water)
STP	12.5 mg/l (Segmentation, Targeting and Positioning)
Soil	0.321 mg/kg (soil)
123-86-4 N-butyl acetate	
Sewage treatment plant	35.6 mg/l (Sewage treatment plant)
Freshwater	0.18 mg/l (Freshwater)
Marine water	0.018 mg/l (Marine water)
Sediment (freshwater)	0.981 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.098 mg/kg sed dw (Marine water)
Intermittent releases	0.36 mg/l (Freshwater)
Soil	0.09 mg/kg (soil)
822-06-0 Hexamethylene diisocyanate	
Sewage treatment plant	8.42 mg/l (Sewage treatment plant)
Freshwater	0.0774 mg/l (Freshwater)
Marine water	0.00774 mg/l (Marine water)
Sediment (freshwater)	0.01334 mg/kg sed dw (Marine water)
Sediment (marine water)	0.001334 mg/kg sed dw (Marine water)
Soil	0.0026 mg/kg (soil)

(Contd. on page 9)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 8)

· Ingredients with biological limit values:

822-06-0 Hexamethylene diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period of exposure

Parameter: isocyanate-derived diamine

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

Filter AX

In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.

· Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information on the breakthrough time of the glove material

provide. The gloves selected should have a breakthrough time of at least 8 hours

have. Nitrile rubber. Viton rubber (fluoro rubber). To protect hands from chemicals, gloves must comply with European Standard EN374.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 10)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 9)

- Eye/face protection



Tightly sealed goggles

- Body protection:
- Skin protection:
Wear suitable protective clothing to protect against splashes or contamination.
For
best protection, clothing should include anti-static overalls, boots and gloves.
- Environmental exposure controls
Keep container tightly closed when not in use regarding restrictions on emissions to air, water and soil.

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- General Information
- Physical state: Liquid
- Colour: Clear
- Odour: Characteristic
- Odour threshold: Not determined
- Melting point/freezing point: Undetermined
- Boiling point or initial boiling point and boiling range: 36 °C (Koolwaterstoffen, C9, aromaten.)
- Flammability: Flammable.
- Lower and upper explosion limit
- Lower: 1.2 Vol % (123-86-4 N-butyl acetate)
- Upper: 7.5 Vol % (123-86-4 N-butyl acetate)
- Flash point: 27 °C
- Auto-ignition temperature: 370 °C (123-86-4 N-butyl acetate)
- Decomposition temperature: Not determined
- pH: Mixture reacts violently with water.
- Viscosity:
- Kinematic viscosity at 20 °C: 50 s (ISO 4 mm)
- Dynamic: Not determined
- Solubility
- water: Fully miscible.
- Partition coefficient n-octanol/water (log value): Not determined
- Vapour pressure at 20 °C: 10.7 hPa (123-86-4 N-butyl acetate)
- Vapour pressure at 50 °C: 55 hPa
- Density and/or relative density
- Density at 20 °C: 1.04116 g/cm³
- Relative density: Not determined

(Contd. on page 11)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 10)

· Vapour density	Not determined
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	22.4 %
· VOC content:	22.37 %
	VOC content:
	232.9 g/l / 1.94 lb/gal
· Solids content:	0 %
· Change in condition	
· Evaporation rate	Not determined
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 12)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 11)

- 10.4 Conditions to avoid
Avoid heat, flames and other sources of ignition. Static electricity and spark formation should be avoided. Do not pressurise, cut, weld, drill, abrade or otherwise expose to heat or sources of ignition.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity
Harmful if inhaled.

- LD/LC50 values relevant for classification:

28182-81-2 Hexamethylene-1,6 diisocyanate homopolymer

Inhalative	LC50 Damp (4 uren)	390 mg/m ³ (rat)
------------	--------------------	-----------------------------

128601-23-0 Hydrocarbons, C9, aromatics.

Oral	LD50	3,492 mg/kg (rat) (OECD 401)
Dermal	LD50	3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	>6,193 mg/m ³ (rat) (OECD 403)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
Dermal	LD50	>5 g/kg (rabbit)
Inhalative	LC50 6 hours	16,000 mg/m ³ (rat)

110-43-0 Heptan-2-one

Oral	Acute toxicity	1,600 mg/kg/bg (rat)
Dermal	Acute toxicity	2,000 mg/kg/bg (rat) (OESO 402)
	Short-term exposure (15 minutes): 100 ppm	475 mg/m ³ (Occupational exposure limits)
Inhalative	Acute toxicity 4 hours	16.7 mg/l (rat) (OESO 403)

123-86-4 N-butyl acetate

Oral	LD50	10,760 mg/kg bw (rat)
Dermal	LD50	>14,000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>20 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Void
- Serious eye damage/irritation Void
- Respiratory or skin sensitisation
May cause an allergic skin reaction.
- Germ cell mutagenicity Void
- Carcinogenicity
Based on available data, the classification criteria are not met.

(Contd. on page 13)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 12)

- Reproductive toxicity
Based on available data, the classification criteria are not met.
- STOT-single exposure
May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure
Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

128601-23-0 Hydrocarbons, C9, aromatics.

EC50/48 h	3.2 mg/l ((Daphnia magna))
LC50 (96 hours)	9.2 mg/l ((rainbow trout))
EC50 (72 hours)	2.9 mg/l (algae) (NOEC)

110-43-0 Heptan-2-one

Vistoxicity (acute) 96 hours	131 mg/l (Thick-headed zip) (EPA OPP 72-1)
ErC50 Algal toxicity 72 hours	98.2 mg/l (Microalgae) (OESO 201)

· 12.2 Persistence and degradability

Persistence and degradability

The product is readily biodegradable.

Biodegradability - 78%: 28 days OECD 301F

· Behaviour in environmental systems:

· Components:

Xylene: Biodegradability;

- Degradation 87.8%: 28 days / OECD 301F

Ethylbenzene: Biodegradability; Degradation 70 - 80%: 28 days

- Degradation 100%: 6 days / OECD 301E

2-methoxy-1-methyl acetate: Biodegradability: 83%; 28 days / Manometric respirometry test (TG 301 F)

· 12.3 Bioaccumulative potential No further relevant information available.

· Bioconcentration factor (BCF)

Xylene BCF: 5.4 - 25.9, Oncorhynchus mykiss (Rainbow trout)

Ethylbenzene BCF: <100, Fish "Read-across" data.

2-methoxy-1-methyl acetate BCF: <100

· 12.4 Mobility in soil The product is not soluble in water.

(Contd. on page 14)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 13)

- 12.5 Results of PBT and vPvB assessment
- PBT:
This substance is not classified as PBT or vPvB according to current EU criteria.
- vPvB:
This substance is not classified as vPvB according to current EU criteria.
- 12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
- ADR 1263 PAINT
- IMDG, IATA PAINT
- 14.3 Transport hazard class(es)
- ADR
- 
- Class 3 (F1) Flammable liquids.

(Contd. on page 15)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 14)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

GB

(Contd. on page 16)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 15)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Poisons Act

- Regulated explosives precursors

None of the ingredients is listed.

- Regulated poisons

None of the ingredients is listed.

- Reportable explosives precursors

None of the ingredients is listed.

- Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t

- National regulations:

- Technical instructions (air):

Class	Share in %
I	<0.3
NK	10-25

- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.

(Contd. on page 17)

Safety data sheet
according to UK REACH

Printing date 04.05.2026

Version number 24 (replaces version 23)

Revision: 04.05.2026

Trade name: Epifanes Pu Speedcoat hardener

(Contd. of page 16)

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

• Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• Department issuing SDS: Research & Development.

• Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

• Sources

ECHA European Chemical Agency - <http://echa.europa.eu/information-on-chemicals>

SDS of raw materials provided by producer/supplier.

DNEL/PNEC/Aquatic toxicity provided according to safety data sheet producer/supplier.

• * Data compared to the previous version altered.